



ATH 2303 M, DN 250 CF-F, External drive electronics, Water cooled, Non-heated

ATH 2303 M, DN 250 CF-F, External drive electronics, Water
cooled, Non-heated








Similar Image

ATH 2303 M, DN 250 CF-F, External drive electronics, Water cooled, Non-heated

- 5-axis magnetically levitated turbopump with drag stage for a pump speed of up to 2150 l/s for N₂
- DN 250 CF-F inlet flange
- Operation with Magpower external drive electronics
- Installation in any orientation
- Water cooled, Non-heated
- CE marked and ROHS compliant



Dimensions



H 398.1 mm

Technical Data	ATH 2303 M, DN 250 CF-F, External drive electronics, Water cooled, Non-heated
Bearing	Magnetically Levitated
Compression ratio for Ar	$> 1 \cdot 10^8$
Compression ratio for H ₂	$> 1 \cdot 10^3$
Compression ratio for He	$> 3 \cdot 10^4$
Compression ratio for N ₂	$> 1 \cdot 10^8$
Cooling method	Water
Cooling water consumption	1 l/m
Cooling water temperature	15-25 °C
Cooling water temperature max.	40 °C 104 °F 313 K
Electronic drive unit	External drive electronics
Flange (in)	DN 250 CF-F
Flange (out)	DN 40 ISO-KF
Fore-vacuum max. for N ₂	2.9 hPa 2.17 Torr 2.9 mbar
Gas throughput for Ar	25.4 hPa l/s 19.05 Torr l/s 25.4 mbar l/s
Gas throughput for H ₂	> 67.6 hPa l/s > 50.7 Torr l/s > 67.6 mbar l/s
Gas throughput for He	> 67.6 hPa l/s > 50.7 Torr l/s > 67.6 mbar l/s
Gas throughput for N ₂	67.6 hPa l/s 50.7 Torr l/s 67.6 mbar l/s
Interfaces	Via External drive electronics
Mounting orientation	in any orientation
Operating voltage	200-240 V AC, 50/60 Hz
Power consumption at ultimate pressure	350 W
Pumping speed for Ar	2000 l/s
Pumping speed for H ₂	1100 l/s
Pumping speed for He	1800 l/s
Pumping speed for N ₂	2150 l/s
Pumping speed range	2300 l/s
Rotation speed $\pm 2\%$	31,000 rpm 31,000 min ⁻¹
Run-up time	< 8 min
Separate electronic drive unit	YES
Ultimate pressure	$< 6 \cdot 10^{-9}$ hPa $< 4.5 \cdot 10^{-9}$ Torr $< 6 \cdot 10^{-9}$ mbar
Weight	60 kg 132.28 lb

Order number	
ATH 2303 M	TMB206220000

Accessories	
Electronic controllers	
Magpower controller	120917
Inlet screen	
Aluminum inlet screen kit for DN250	111640
Stainless inlet screen kit for DN250 - M 5	108762
Interconnecting cable (pump to Magpower external drive electronics)	
Interconnecting cable (pump to Magpower external drive electronics), L = 1.0 m	A215300-010-C6-D
Interconnecting cable (pump to Magpower external drive electronics), L = 10.0 m	A215300-100-C6-D
Interconnecting cable (pump to Magpower external drive electronics), L = 20.0 m	A215300-200-C6-D
Interconnecting cable (pump to Magpower external drive electronics), L = 3.5 m	A215300-035-C6-D
Interconnecting cable (pump to Magpower external drive electronics), L = 5.0 m	A215300-050-C6-D
Mounting kits	
Mounting bolts for CF-F (for ATH 500 M, DN100/160; ATH 2300 M, DN 200/250)	118690
Power cord	
Power cord 2.5 m Europe standard 200 - 240 V AC	A328405
Power cord 2.5 m US standard 200 - 240 V AC	A331729
Rotatable flange	
Rotatable flange DN250 CF-F	303133
Valve cable (external drive electronics to venting valve)	
Valve cable (Magpower external drive electronics to venting valve), L = 1.0 m	A462403-010
Valve cable (Magpower external drive electronics to venting valve), L = 10.0 m	A462403-100
Valve cable (Magpower external drive electronics to venting valve), L = 20.0 m	A462403-200
Valve cable (Magpower external drive electronics to venting valve), L = 3.5 m	A462403-035
Valve cable (Magpower external drive electronics to venting valve), L = 5.0 m	A462403-050
Venting valves and other accessories	
Air venting valve (for OBC V4 and Magpower)	114280
Dust filter	106229
Purge valve 50 sccm	111921S
Water inlet valve 24 V DC	108668

上海伯东--您理想的真空合作伙伴!

伯东公司成立于1953年,全球范围内有一千七百名员工。伯东企业(上海)有限公司(www.hakuto-vacuum.cn)主要从事半导体设备、电子零部件加工、销售及相关服务工作,集团年营业额约为100亿人民币。伯东公司在国内主要城市:北京、苏州、广州、深圳、成都及厦门设有营业据点。

上海伯东真空产品事业部秉承为广大中国客户提供世界一流的真空产品、推动中国真空工艺发展、承担企业社会责任为经营理念,已累计为超过10,000家企业提供真空服务,覆盖工业、半导体、镀膜、科研和分析行业。

上海伯东代理品牌包含:德国Pfeiffer全系列真空产品、美国KRI离子源、美国Brooks Polycold制冷机,美国HVA真空阀门,美国inTEST(Temptronic)高速温度循环测试机,离子蚀刻机,真空镀膜系统及配套真空零配件等。

上海伯东作为国际知名真空品牌指定授权代理商,全权负责在中国地区的销售和维修服务,100%使用原厂进口零部件以及国外受训维修工程师;拥有完全的拆解,维修,校正能力并提供24小时在线服务。



Are you looking for a
perfect vacuum solution?
Please contact us:

伯东企业(上海)有限公司
T +021 5046-3511
ec@hakuto-vacuum.cn



www.hakuto-vacuum.cn
www.hakuto-vacuum.com.tw

