



ATH 2303 M, DN 250 ISO-F, OBC V4 integrated drive electronics, Profibus, Water cooled, Non-heated

ATH 2303 M, DN 250 ISO-F, OBC V4 integrated drive electronics, Profibus, Water cooled, Non-heated








Similar Image

ATH 2303 M, DN 250 ISO-F, OBC V4 integrated drive electronics, Profibus, Water cooled, Non-heated

- 5-axis magnetically levitated turbopump with drag stage for a pump speed of up to 2150 l/s for N₂
- DN 250 ISO-F inlet flange
- Operation with OBC V4 integrated drive electronics
- Installation in any orientation
- Profibus, Water cooled, Non-heated
- CE marked and ROHS compliant



Dimensions



H 343.5 mm

Technical Data

ATH 2303 M, DN 250 ISO-F, OBC V4 integrated drive electronics, Profibus, Water cooled, Non-heated

Bearing	Magnetically Levitated
Compression ratio for Ar	$> 1 \cdot 10^8$
Compression ratio for H ₂	$> 1 \cdot 10^3$
Compression ratio for He	$> 3 \cdot 10^4$
Compression ratio for N ₂	$> 1 \cdot 10^8$
Cooling method	Water
Cooling water consumption	1 l/m
Cooling water temperature	15-25 °C
Cooling water temperature max.	40 °C 104 °F 313 K
Electronic drive unit	Integrated drive electronics
Flange (in)	DN 250 ISO-F
Flange (out)	DN 40 ISO-KF
Fore-vacuum max. for N ₂	2.9 hPa 2.17 Torr 2.9 mbar
Gas throughput for Ar	25.4 hPa l/s 19.05 Torr l/s 25.4 mbar l/s
Gas throughput for H ₂	> 67.6 hPa l/s > 50.7 Torr l/s > 67.6 mbar l/s
Gas throughput for He	> 67.6 hPa l/s > 50.7 Torr l/s > 67.6 mbar l/s
Gas throughput for N ₂	67.6 hPa l/s 50.7 Torr l/s 67.6 mbar l/s
Integrated power supply	YES
Interfaces	Profibus
Mounting orientation	in any orientation
Operating voltage	200-240 V AC, 50/60 Hz
Power consumption at ultimate pressure	350 W
Protection category	IP 54
Pumping speed for Ar	2000 l/s
Pumping speed for H ₂	1100 l/s
Pumping speed for He	1800 l/s
Pumping speed for N ₂	2150 l/s
Pumping speed range	2300 l/s
Rotation speed $\pm 2\%$	31,000 rpm 31,000 min ⁻¹
Run-up time	< 8 min
Ultimate pressure	$< 6 \cdot 10^{-9}$ hPa $< 4.5 \cdot 10^{-9}$ Torr $< 6 \cdot 10^{-9}$ mbar
Weight	68 kg 149.91 lb

Order number	
ATH 2303 M	TMBBB662005A

Accessories	
Electronic controllers	
Hand Held Remote (HHR) with cable	114461
Inlet screen	
Aluminum inlet screen kit for DN250	111640
Stainless inlet screen kit for DN250 - M 5	108762
Mounting kits	
Mounting bolts for ISO-F (for ATH 2300 M, DN 250; ATH 2800 M, DN 250) with centering ring	110034
Mounting bolts for ISO-F (for ATH 500 M, DN160; ATH 1600 M, DN 200/250; ATH 2300 M, ATH 2800 M, ATH 2804 M, DN 250) without centering ring	110676S
Venting valves and other accessories	
Air venting valve (for OBC V4 and Magpower)	114280
Dust filter	106229
Purge valve 50 sccm	111921S
Water inlet valve 24 V DC	108668

上海伯东--您理想的真空合作伙伴!

伯东公司成立于1953年,全球范围内有一千七百名员工。伯东企业(上海)有限公司(www.hakuto-vacuum.cn)主要从事半导体设备、电子零部件加工、销售及相关服务工作,集团年营业额约为100亿人民币。伯东公司在国内主要城市:北京、苏州、广州、深圳、成都及厦门设有营业据点。

上海伯东真空产品事业部秉承为广大中国客户提供世界一流的真空产品、推动中国真空工艺发展、承担企业社会责任为经营理念,已累计为超过10,000家企业提供真空服务,覆盖工业、半导体、镀膜、科研和分析行业。

上海伯东代理品牌包含:德国Pfeiffer全系列真空产品、美国KRI离子源、美国Brooks Polycold制冷机,美国HVA真空阀门,美国inTEST(Temptronic)高速温度循环测试机,离子蚀刻机,真空镀膜系统及配套真空零配件等。

上海伯东作为国际知名真空品牌指定授权代理商,全权负责在中国地区的销售和维修服务,100%使用原厂进口零部件以及国外受训维修工程师;拥有完全的拆解,维修,校正能力并提供24小时在线服务。



Are you looking for a
perfect vacuum solution?
Please contact us:

伯东企业(上海)有限公司
T +021 5046-3511
ec@hakuto-vacuum.cn



www.hakuto-vacuum.cn
www.hakuto-vacuum.com.tw

