



HiPace[®] 30

**Smallest yet powerful turbo molecular pump
without Holweck-stage with a pumping speed of
up to 34 l/s for N₂**







Similar Image

HiPace® 30 with TC 110, DN 63 CF-F

- Small yet powerful turbopump with a pumping speed of up to 32 l/s for N₂
- Highest compression in this pumping speed class
- Simple integration into small analytical systems
- Low weight, ideal for mobile applications
- Long maintenance intervals for a long life cycle
- For installation in any orientation
- Integrated TC 110 drive electronics
- Extensive accessories expand the range of applications



Dimensions



Technical Data	HiPace® 30 with TC 110, DN 63 CF-F
Compression ratio for Ar	$> 1 \cdot 10^{11}$
Compression ratio for H ₂	$3 \cdot 10^5$
Compression ratio for He	$3 \cdot 10^7$
Compression ratio for N ₂	$> 1 \cdot 10^{11}$
Cooling method, optional	Air/Water
Cooling method, standard	Convection
Cooling water consumption	75 l/h
Cooling water temperature	5-25 °C 41-77 °F 278-298 K
Electronic drive unit	with TC 110
Flange (in)	DN 63 CF-F
Flange (out)	DN 16 ISO-KF / G 1/4"
Fore-vacuum max. for N ₂	32 hPa 24 Torr 32 mbar
Gas throughput at full rotational speed for Ar	0.22 hPa l/s 0.17 Torr l/s 0.22 mbar l/s
Gas throughput at full rotational speed for H ₂	10 hPa l/s 7.5 Torr l/s 10 mbar l/s
Gas throughput at full rotational speed for He	1.84 hPa l/s 1.38 Torr l/s 1.84 mbar l/s

Technical Data		HiPace® 30 with TC 110, DN 63 CF-F
Gas throughput at full rotational speed for N ₂		0.66 hPa l/s 0.49 Torr l/s 0.66 mbar l/s
Interfaces		RS-485, Remote
Mounting orientation		in any orientation
Operating voltage		24 (± 5 %) V DC
Permissible magnetic field max.		3 mT
Protection category		IP54
Pumping speed for Ar		32 l/s
Pumping speed for H ₂		20 l/s
Pumping speed for He		24 l/s
Pumping speed for N ₂		32 l/s
Rotation speed ± 2 %		90000 min ⁻¹
Rotation speed variable		50-100 %
Run-up time		1.7 min
Sound pressure level		≤ 48 dB (A)
Ultimate pressure according to PNEUROP		< 5 · 10 ⁻¹⁰ hPa < 3.75 · 10 ⁻¹⁰ Torr < 5 · 10 ⁻¹⁰ mbar
Venting connection		G 1/8"
Weight		3.2 kg 7.05 lb

Order number	
HiPace® 30	PM P05 281

Accessories	
Accessory for TC 110	
Coupling set	PM 061 682 -X
Enclosure for plug, spraywater-protected, 15-pole, D-sub	P 0998 016
TCS 11, adapter for TC 110/120 with RS-485 interface	PM 061 636 -U
TCS 12, adapter for TC 110/120 with interface RS-485, 4 accessory ports and coupling set	PM 061 638 -U
TCS 13, adapter for TC 110/120 with interface RS-485, 2 accessory ports and coupling set	PM 061 856 -U
Adapter and control cables	
Connection cable TPS 180 - MVP 006-4 with HiPace 80/HiPace 10, 2 x 0.5 m	PM 061 399 -T
Control cable for valve	PM 061 687 -T
HiPace - ACP connection cable	PM 071 142 -X
Air cooling	
Air cooling for HiPace 30 with TC 110	PM Z01 348
CF-F, Sealings, splinter shields, protection screens	
Protection screen for DN 63 CF-F	PM 016 333
Splinter shield for turbopumps, DN 63 CF-F	PM 016 312
Connection cables	
Connection cable for HiPace with TC 110/120	PM 061 543 -T
Connection cable incl. 2 accessory ports for TC 110/120 to power supply	PM 061 552 -T
Connection cable with RS-485 interface and 2 accessory ports for TC110/120 to power supply	PM 061 351 -T
Connection cable with RS-485 interface and 3 accessory ports for TC 110/120 to power supply	PM 061 512 -T
Connection cable with RS-485 interface for TC 110/120 to power supply	PM 061 350 -T
Control and display units	
Accessories package for HPU 001/PC	PM 061 005 -T
DCU 002, Display Control Unit	PM 061 348 -T
HPU 001, Handheld Programming Unit	PM 051 510 -T
RJ 45 interface cable on M12 for HiPace	PM 051 726 -T
DCU with integrated power supply	
DCU 110, Display control unit incl. power supply	PM C01 820
DCU 180, Display control unit incl. power supply	PM C01 821
Fore-vacuum safety valves	
TVV 001 fore-vacuum safety valve, 115 V AC	PM Z01 206
TVV 001 fore-vacuum safety valve, 230 V AC	PM Z01 205
Interface and extension cables	
Extension cable M8 on M8	PM 061 783 -T
Interface cable, M12 m straight/ M12 m angled 0.7 m	PM 061 791 -T
Interface cable, M12 m straight / M12 m straight, 3 m	PM 061 283 -T
Mains cables	
Mains cable 115 V AC, NEMA 5-15 to C13, 3 m	P 4564 309 ZE
Mains cable 208 V AC, NEMA 6-15 to C13, 3 m	P 4564 309 ZF
Mains cable 230 V AC, CEE 7/7 to C13, 3 m	P 4564 309 ZA
Power failure venting units (normally open)	
Shielded power failure venting unit, 24 V DC, G 1/8", for connection to TC 110/120	PM Z01 330
Relay boxes	
Relay box, shielded, for backing pumps, 1-phase 7A for TC 110/120 and TCP 350, plug M8	PM 071 282 -X
Relay box for backing pump, single phase 20 A for TC 110/120 and TCP 350, M8 plug	PM 061 373 -T

Accessories	
RS-485	
Connector M12 to RS-485	PM 061 270 -X
Power separator for RS-485	PT 348 132 -T
Termination resistor for RS-485	PT 348 105 -T
USB converter to RS-485 interface	PM 061 207 -T
Y-Connector M12 to RS-485	P 4723 010
Sealing gas	
Sealing gas throttle for HiPace 60/80	PM Z01 316
Sealing gas valve, shielded for HiPace 60/80 with TC 110	PM Z01 310
TPS-19" rack module	
Front panel kit for TPS 111	PM 061 393 -T
Front panel kit for TPS 181	PM 061 394 -T
TPS 111, mains pack 19" rack module 3HU	PM 061 344 -T
TPS 181, mains pack 19" rack module 3HU	PM 061 345 -T
TPS wall rail fitting	
TPS 110, mains pack for wall/standard rail fitting	PM 061 340 -T
TPS 180, mains pack for wall/standard rail fitting	PM 061 341 -T
Wall rail fitting for TPS 110/180/310/400	PM 061 392 -T
Venting accessory with small flange, G 1/8", hoses, air drier	
Banjo fitting	PM 016 787 -T
Banjo fitting, small	PM 143 877 -T
Hose nozzle for 9 mm hose, G 1/8"	PM 016 783 -T
Plug-in fitting for 6 mm hose, G 1/8"	PM 016 781 -T
Plug-in fitting for 8 mm hose, G 1/8"	PM 016 782 -T
Screw-in flange, DN 10 ISO-KF, G 1/8"	PM 033 737 -T
Screw-on flange, DN 16 ISO-KF, G 1/8"	PM 016 780 -T
TTV 001, dryer for venting turbopumps	PM Z00 121
Venting valve (normally closed)	
Venting valve, 24 V DC, G 1/8" without cable	PM Z01 293
Venting valve, shielded, 24 V DC, G 1/8", for connection to TC 110/120	PM Z01 290
Vibration damper	
Vibration damper for HiPace 60/80, DN 63 CF-F	PM 006 801 -X