

Duo 10 M

Dual-stage rotary vane pumps with a pumping speed of up to 12 m³/h:





Similar Image



Duo 10 M, 3-phase motor, 3TF, 220-240/380-420 V, 50 Hz; 250-277/440-480 V, 60 Hz

- Dual-stage, high-performance rotary vane pump with a pumping speed of up to 12 m³/h
- With 3-phase motor
- With temperature sensor (3TF) for optimum motor protection
- Integrated gas ballast and HV safety valve
- For all low and medium vacuum applications
- Magnetically coupled
- Special feature: Various motor voltages for worldwide employment


M = Magnetically coupled

MC = Corrosive gas version, magnetically coupled

TF = Temperature sensor



Dimensions



Technical Data	Duo 10 M, 3-phase motor, 3TF, 220-240/380-420 V, 50 Hz; 250-277/440-480 V, 60 Hz
Ambient temperature	12-40 °C 53.6-104 °F 285-313 K
Cooling method, standard	Air
Emission sound pressure level without gas ballast at 50 Hz	≤ 55 dB (A)
Exhaust pressure, max.	1,500 hPa 1,125 Torr 1,500 mbar
Exhaust pressure, min.	250 hPa 187.5 Torr 250 mbar
Flange (in)	DN 25 ISO-KF
Flange (out)	DN 25 ISO-KF
Leak rate safety valve	≤ 1 · 10 ⁻⁵ Pa m ³ /s ≤ 7.5 · 10 ⁻⁵ Torr l/s ≤ 1 · 10 ⁻⁴ mbar l/s
Magnetic coupling	yes
Mains requirement: voltage 50 Hz	220-240/380-420 (± 5 %) V
Mains requirement: voltage 60 Hz	250-277/440-480 (± 5 %) V
Motor version	3-phase Motor
Operating fluid	P3
Operating fluid filling	1 l
Protection category	IP 54
Pumping speed at 50 Hz	10 m ³ /h
Pumping speed at 60 Hz	12 m ³ /h
Rated power 50 Hz	0.37 kW
Rated power 60 Hz	0.44 kW
Rotation speed at 50 Hz	1500 min ⁻¹
Rotation speed at 60 Hz	1800 min ⁻¹
Ultimate pressure with gas ballast	6 · 10 ⁻³ hPa 4.5 · 10 ⁻³ Torr 6 · 10 ⁻³ mbar
Ultimate pressure without gas ballast	3 · 10 ⁻³ hPa 2.25 · 10 ⁻³ Torr 3 · 10 ⁻³ mbar
Weight	24 kg 52.91 lb

Typical ultimate pressure according to PNEUROP

Order number

Duo 10 M

PK D62 105

Accessories	
Accessories	
FAK 025, activated carbon filter	PK Z30 006
KAS 25, condensate separator for pumping speeds up to 12 m ³ /h	PK Z10 032
ONF 25 M, oil mist filter for pumping speeds of up to 12 m ³ /h	PK Z40 157
ONF 25 S, oil mist filter for pumping speeds of up to 12 m ³ /h	PK Z40 004
ZFO 025, zeolite trap	PK Z70 006
Accessories UnoLine	
KLF 025, cold trap	PK Z80 006
Oil pressure switch for Duo 5/10/20 M and Penta 20/35	PK 196 484 -T
Operations monitoring unit 1 for Duo 1.6/3/6/11 and Duo 5/10/20 M	PK 196 157 -T
Operations monitoring unit 2 for Duo 1.6/3/6/11 and Duo 5/10/20 M	PK 196 142 -T
Operations monitoring unit 3 for Duo 1.6/3/6/11 and Duo 5/10/20 M	PK 196 141 -T
SAS 25, DN 25 ISO-KF, polyester filter	PK Z60 508
URB 025, catalytic trap, 115 V	PT U10 761
URB 025, catalytic trap, 230 V	PT U10 760
Accessories UnoLine Plus	
PTC-resistor tripping device	P 4768 051 FQ
Consumables	
P3, mineral oil, 1 l	PK 001 106 -T
P3, mineral oil, 5 l	PK 001 107 -T
P3, mineral oil, 20 l	PK 001 108 -T