



Duo 20 M

Dual-stage rotary vane pumps with a pumping speed up to 24 m³/h :





Similar Image



Duo 20 MC, 1-phase motor, 200-230 V, 50 Hz; 200-240 V, 60 Hz

- Dual-stage, high-performance rotary vane pump with a pumping speed up to 24 m³/h
- With Single-phase motor
- Integrated gas ballast and HV safety valve
- For all low and medium vacuum applications
- Corrosive gas version, magnetically coupled
- Special feature: Various motor voltages for worldwide employment
- Other motor voltages available on request


M = Magnetically coupled

MC = Corrosive gas version, magnetically coupled

TF = Temperature sensor



Dimensions



Technical Data	Duo 20 MC, 1-phase motor, 200-230 V, 50 Hz; 200-240 V, 60 Hz
Ambient temperature	12-40 °C 53.6-104 °F 285-313 K
Cooling method, standard	Air
Corrosive gas version	yes
Emission sound pressure level without gas ballast at 50 Hz	≤ 57 dB (A)
Exhaust pressure, max.	1,500 hPa 1,125 Torr 1,500 mbar
Exhaust pressure, min.	250 hPa 187.5 Torr 250 mbar
Flange (in)	DN 25 ISO-KF
Flange (out)	DN 25 ISO-KF
Leak rate magnetic coupling	≤ 1 · 10 ⁻⁶ Pa m ³ /s ≤ 7.5 · 10 ⁻⁶ Torr l/s ≤ 1 · 10 ⁻⁵ mbar l/s
Leak rate safety valve	≤ 1 · 10 ⁻⁵ Pa m ³ /s ≤ 7.5 · 10 ⁻⁵ Torr l/s ≤ 1 · 10 ⁻⁴ mbar l/s
Magnetic coupling	yes
Mains cable	yes
Mains requirement: voltage (selectable)	100-110, 50 Hz; 100-120, 60 Hz V
Mains requirement: voltage 50 Hz	200-230 (± 5 %) V
Mains requirement: voltage 60 Hz	200-240 (± 5 %) V
Motor version	1-phase Motor
Operating fluid	F4
Operating fluid filling	1.1 l
Protection category	IP 54
Pumping speed at 50 Hz	20 m ³ /h
Pumping speed at 60 Hz	24 m ³ /h
Rated power 50 Hz	0.75 kW
Rated power 60 Hz	0.90 kW
Rotation speed at 50 Hz	1500 min ⁻¹
Rotation speed at 60 Hz	1800 min ⁻¹
Switch	Yes, with 2 m mains cable and safety plug
Ultimate pressure with gas ballast	7 · 10 ⁻³ hPa 5.25 · 10 ⁻³ Torr 7 · 10 ⁻³ mbar
Ultimate pressure without gas ballast	4 · 10 ⁻³ hPa 3 · 10 ⁻³ Torr 4 · 10 ⁻³ mbar
Weight	44 kg 97 lb

Typical ultimate pressure according to PNEUROP

Order number

Duo 20 M

PK D63 732

Accessories	
Accessories	
KAS 25 C, condensate separator, corrosive version for pumping speeds up to 34 m ³ /h	PK Z10 406
Oil return unit from ONF 25 M, 25 L, 25 XL	PK 196 177 -T
ONF 025 C, oil mist filter, corrosive gas version up to 24 m ³ /h	PK Z40 406
Accessories UnoLine	
KLF 025, cold trap	PK Z80 006
Oil pressure switch for Duo 5/10/20 M and Penta 20/35	PK 196 484 -T
Operations monitoring unit 1 for Duo 1.6/3/6/11 and Duo 5/10/20 M	PK 196 157 -T
Operations monitoring unit 2 for Duo 1.6/3/6/11 and Duo 5/10/20 M	PK 196 142 -T
Operations monitoring unit 3 for Duo 1.6/3/6/11 and Duo 5/10/20 M	PK 196 141 -T
Accessories UnoLine Plus	
PTC-resistor tripping device	P 4768 051 FQ
Consumables	
F4, Perfluoropolyether, 0.25 l	PK 005 885 -T
F4, Perfluoropolyether, 0.5 l	PK 005 886 -T
F4, Perfluoropolyether, 1 l	PK 005 887 -T