

ASM 192 T2D+

Console leak detector with 1 or 2 ACP dry pumps, offering 25 m^3/h or 50 m^3/h backing capacity

Hakuto 伯東

PFEIFFER VACUUM



Similar Image


ASM 192 T2D+, 25 m³/h, remote control in mbar l/s, English language, 110/130 V and US power cable (15 A)

- Frictionless ACP dry pump with 25 m³/h backing capacity
- 20 l/s helium pumping speed
- 110/130 V operating voltage
- US power cable (15 A)
- Voice synthesizer in English
- Remote control in mbar l/s

Three masses leak detection instead of only helium available upon request

Metal seals on the analyzer cell available upon request

Dimensions



Technical Data	ASM 192 T2D+, 25 m³/h, remote control in mbar l/s, English language, 110/130 V and US power cable (15 A)
Backing pump	with oil free backing pump
Backing pump capacity	25 m³/h
Detectable gases	^{4}He
Dimensions (L x W x H)	594 x 692 x 933 mm | 23.39 x 27.24 x 36.73 inch
Flange (in)	DN 50 ISO-KF

Technical Data	ASM 192 T2D+, 25 m^3/h, remote control in mbar l/s, English language, 110/130 V and US power cable (15 A)
I/O interfaces	Digital inputs (Start, Vent, Calibration…); Digital outputs (Test modes, cycle in progress, helium signal above reject set point…); Analog outputs (Helium signal log, Inlet pressure)
Interface	RS-232
Language	English
Mains cable	US power cable (15 A)
Max. inlet test pressure	30 hPa | 22.5 Torr | 30 mbar
Minimum detectable leak rate for helium (sniffing leak detection)	$1 \cdot 10^{-8}$ Pa m^3/s | $7.5 \cdot 10^{-8}$ Torr l/s | $1 \cdot 10^{-7}$ mbar l/s
Minimum detectable leak rate for helium (vacuum leak detection)	$5 \cdot 10^{-13}$ Pa m^3/s | $3.75 \cdot 10^{-12}$ Torr l/s | $5 \cdot 10^{-12}$ mbar l/s
Noise level	66 dB (A)
Operating temperature	10-40 °C | 50-104 °F | 283-313 K
Pumping speed for He	20 l/s
Start-up time (20°C) with calibration	5 min
Start-up time (20°C) without calibration	3.5 min
Supply	110-130 V, 50/60 Hz
Test method	Vacuum and sniffing leak detection
Type	High Performance - Console
User interface	Graphic color touch screen
Weight	157 kg | 346.12 lb

Order number	
ASM 192 T2D+	**D30R0S0MB710**