


Hena 26




Hena 26, 190-208/380-415; 220-230/440-460 V

- Powerful rotary vane pump with a pumping speed up to 120 m³/h
- 3-phase motor for 190-208/380-415 V, 50 Hz; 220-230/440-460 V, 60 Hz
- Integrated safety valve
- For all low and medium vacuum applications
- Gas ballast permanently open, ball valve available as accessory



Dimensions



Technical Data	Hena 26, 190-208/380-415; 220-230/440-460 V
Ambient temperature	12-40 °C 53.6-104 °F 285-313 K
Cooling method, standard	Air
Dimensions (L x W x H)	588 x 284 x 272 mm ³
Emission sound pressure level without gas ballast at 50 Hz	≤60 dB (A)
Emission sound pressure level without gas ballast at 60 Hz	≤63 dB (A)
Exhaust pressure, max.	Atmospheric pressure
Exhaust pressure, min.	Atmospheric pressure
Flange (in)	Female thread G 1 1/4"
Flange (out)	Female thread G 1 1/4"
Gas ballast	yes, without shut-off valve
Leak rate safety valve	≤ 8 · 10 ⁻³ Pa m ³ /s ≤ 6 · 10 ⁻² Torr l/s ≤ 8 · 10 ⁻² mbar l/s
Mains requirement: voltage (range)	±5 %
Mains requirement: voltage 50 Hz	190-208/380-415 V
Mains requirement: voltage 60 Hz	220-230/440-460 V
Operating fluid	P3
Operating fluid filling	1 l
Protection category	IP55
Pumping speed at 50 Hz	25 m ³ /h
Pumping speed at 60 Hz	30 m ³ /h
Rated power 50 Hz	1 kW
Rated power 60 Hz	1.2 kW
Rotation speed at 50 Hz	1500 min ⁻¹
Rotation speed at 60 Hz	1800 min ⁻¹
Ultimate pressure with gas ballast	1.5 hPa 1.12 Torr 1.5 mbar
Ultimate pressure without gas ballast	0.3 hPa 0.23 Torr 0.3 mbar
Weight	35 kg 77.16 lb

Order number	
Hena 26	PK D03 200

Accessories	
Accessories	
FAK 040, activated carbon filter	PK Z30 008
KAS 40, condensate separator for pumping speeds up to 120 m ³ /h	PK Z10 008
Accessories HenaLine	
Flange DN 40 ISO-K - G 1 1/4"	PK 300 525
P3, mineral oil, 1 l	PK 001 106 -T
P3, mineral oil, 20 l	PK 001 108 -T
P3, mineral oil, 5 l	PK 001 107 -T
Pressure gauge for monitoring the operating fluid separator G 3/4"	PK 100 126
SAS 40, dust separator, DN 40 ISO-KF, polyester filter	PK Z60 510

上海伯东--您理想的真空合作伙伴!

伯东公司成立于1953年，全球范围内有一千七百名员工。伯东企业(上海)有限公司(www.hakuto-vacuum.cn)主要从事半导体设备、电子零部件加工、销售及相关服务工作，集团年营业额约为100亿人民币。伯东公司在国内主要城市：北京、苏州、广州、深圳、成都及厦门设有营业据点。

上海伯东真空产品事业部秉承为广大中国客户提供世界一流的真空产品、推动中国真空工艺发展、承担企业社会责任为经营理念，已累计为超过10,000家企业提供真空服务，覆盖工业、半导体、镀膜、科研和分析行业。

上海伯东代理品牌包含：德国Pfeiffer全系列真空产品、美国KRI离子源、美国Brooks Polycold制冷机，美国HVA真空阀门，美国inTEST(Temptronic)高速温度循环测试机，离子蚀刻机，真空镀膜系统及配套真空零配件等。

上海伯东作为国际知名真空品牌指定授权代理商，全权负责在中国地区的销售和维修服务，100%使用原厂进口零部件以及国外受训维修工程师；拥有完全的拆解，维修，校正能力并提供24小时在线服务。



Are you looking for a
perfect vacuum solution?
Please contact us:

伯东企业(上海)有限公司
T +021 5046-3511
ec@hakuto-vacuum.cn



www.hakuto-vacuum.cn
www.hakuto-vacuum.com.tw

PFEIFFER  VACUUM

 伯東